

**TECHNICAL DATA SHEET****T Cleaner 75****Neutral Cleaner for use in Washing Machines**

<b>Description</b>	A neutral liquid cleaner suitable for use in single stage washing machines.						
<b>Features</b>	<ul style="list-style-type: none"><li>• Nitrite-free.</li><li>• Easy-to-use liquid product.</li><li>• Oils &amp; greases not emulsified and can be skimmed off to extend bath life.</li><li>• Non-staining.</li><li>• Rinsing often unnecessary.</li><li>• Contains organic inhibitors which will prevent the rusting of cleaned components for short-term internal storage.</li></ul>						
<b>Product Code</b>	<b>MP0419.</b>						
<b>SG</b>	1.18 ± 0.1 kg/l at 20°C.						
<b>Coverage</b>	<p>The consumption rate will depend on the oiliness of the work. As a guide, the following has proved reliable:</p> <p>Spray Washer: 150 – 200 m<sup>2</sup>/kilo of T Cleaner 75.</p>						
<b>Equipment</b>	Normally, mild steel equipment can be used.						
<b>Initial Fill</b>	<p>For every 1000 litres of tank:</p> <ol style="list-style-type: none"><li>1. Add approximately 750 litres of mains water and heat to temperature.</li><li>2. Add 20 litres of T Cleaner 75 and run the spray pump to circulate the solution and ensure mixing.</li><li>3. Top up tank with water to operating level.</li></ol>						
<b>Application</b>	<p>The process sequence is normally:</p> <ol style="list-style-type: none"><li>1. Clean with T Cleaner 75.</li><li>2. Rinse and allow to dry. A hot rinse will give faster drying.</li><li>3. Continue to next process.</li></ol>						
<b>Control Points</b>	<table><tr><td>Pointage:</td><td>8 – 12 ml</td></tr><tr><td>Temperature</td><td>35° - 75°C</td></tr><tr><td>Time:</td><td>2 - 5 min.</td></tr></table>	Pointage:	8 – 12 ml	Temperature	35° - 75°C	Time:	2 - 5 min.
Pointage:	8 – 12 ml						
Temperature	35° - 75°C						
Time:	2 - 5 min.						
<b>Analytic Control</b>	<p>The bath is primarily controlled by a Pointage Titration carried out routinely according to usage and after the tank has been brought up to normal operating level with water.</p> <p><b>Pointage:</b> measure 10 ml of the tank into a flask and add approximately 100 ml of water. Add 6 – 8 drops of Bromophenol Blue Indicator solution. Titrate with 0.1 M hydrochloric acid until a colour change from blue to yellow is observed.</p> <p><b>Replenishment:</b> Add 1.8 litres of T Cleaner 75 per 1000 litres of tank for each point below the operating level.</p> <p>A Test Kit (<b>MP0609</b>) containing all the necessary items and replacement chemicals is available from Trimite.</p>						

**TECHNICAL DATA SHEET****T Cleaner 75****Neutral Cleaner for use in Washing Machines**

<b>Rinsing</b>	Rinse the work thoroughly in water.
<b>Drying</b>	Normally, air drying is sufficient, but warm air may be used to increase production speeds.
<b>Tank Maintenance</b>	Oil and solids build up should be periodically removed, manually or with an oil skimmer.
<b>Shelf Life</b>	2 years from date of manufacture when correctly stored in unopened containers.
<b>Storage</b>	The product should be stored in cool, dry, frost-free conditions, in sealed containers.
<b>Health &amp; Safety</b>	<b>Refer to the product's Safety Data Sheet and safety advice on the product label before use.</b>
<b>Technical Support</b>	For technical support in using this product, please contact: e: <a href="mailto:birminghamtech@trimite.com">birminghamtech@trimite.com</a> , or t: 0121 554 7000.
<b>Date of Issue</b>	Sep 2021.

Information provided in this leaflet is given in good faith but without warranty or assumed liability, as the conditions of application and use are beyond our control. Data are accurate to the best of our knowledge at the time of issue but may be revised in the light of new knowledge and the user should check that data are current before use. The user must satisfy themselves about the product's suitability for their own purpose and refer to the Safety Data Sheet for this product before use. For industrial use only unless specifically stated otherwise.