

Trimite T Cleaner 5

Solvent Cleaner for Steel and Aluminium

Description	A liquid cleaner for the removal of a wide range of oils and grease from metal surfaces prior to painting or pretreatment processes.
Features	<ul style="list-style-type: none">• Normally applied by hand.• Conforms to BS ISO 27831-1:2008, BS ISO 27831-2:2008 and DEF STAN 03-02/3 Method A.2.• Suitable for all metals - no chemical attack.• No ozone depleting chemicals used.• Fast drying with wide dissolution characteristics - rapid work throughput.• High Workplace Exposure Limits - reduced inhalation hazard.• Can be used on some thermoset plastics.• Can be used for equipment cleaning - reduced user inventory.• Low photochemical potential of ingredients - minimises possibility of smog generation.
Product Code	MP0122.
Coverage	The consumption of the cleaner will depend on the care taken in use and the condition of the surfaces to be cleaned. Practical evaluations have indicated that, when used as recommended below, 1 litre of T Cleaner 5 can satisfactorily remove production oils from about 20 m ² of metal surface.
Application	<p>Normally, effective cleaning is achieved by simple wiping methods. The following notes may assist in optimising the process whilst minimising any solvent emissions:</p> <ol style="list-style-type: none">1. T Cleaner 5 should be used to dampen the cleaning cloth, do not pour it onto the surface to be cleaned.2. Cloths that have not become too contaminated can be stored in an air-tight container and may be used for the initial cleaning of heavily soiled surfaces.3. Folding the cloth to form a pad and progressively re-folding to use a clean area of the material, using both sides, will ensure maximum economy.
Drying	Most surfaces will be dry for painting or pretreatment within 1 min, at normal factory temperatures.
Flash Point	Below 21°C – low flash material . Ensure DSEAR requirements are met before use.
Shelf Life	Min. 1 year from date of delivery when correctly stored in unopened containers.

TECHNICAL DATA SHEET

Trimite T Cleaner 5

Solvent Cleaner for Steel and Aluminium

Storage	The product should be stored in cool, dry, frost-free conditions, in sealed containers.
Health & Safety	Refer to the product's Safety Data Sheet and safety advice on the product label before use.
Technical Support	For technical support in using this product, please contact: e: belfast.sales@trimite.com , or t: +44 (0)28 9066 3361.
Date of Issue	Jan 2025.

Information provided in this leaflet is given in good faith but without warranty or assumed liability, as the conditions of application and use are beyond our control. Data are accurate to the best of our knowledge at the time of issue but may be revised in the light of new knowledge and the user should check that data are current before use. The user must satisfy themselves about the product's suitability for their own purpose and refer to the Safety Data Sheet for this product before use. For industrial and professional use only unless specifically stated otherwise.