

**TECHNICAL DATA SHEET****Trimite T Cleaner 8****WB Degreaser**

<b>Description</b>	An effective water based, manual cleaner and degreaser for metals.
<b>Features</b>	<ul style="list-style-type: none"><li>• An effective replacement for solvent based degreasers.</li><li>• Simple wipe on/wipe off manual application at ambient temperatures.</li><li>• Mild rust-retarding properties to help preserve cleaned metal surfaces.</li><li>• Conforms to BS7773 (1995) 3.2.3.B2 and DEF STAN 03/4 Process B.1.</li><li>• Water based - no flammable restrictions in normal use.</li><li>• Mild odour for operator comfort.</li><li>• Works with all normal tap waters.</li><li>• High WEL Standard ingredients – low inhalation hazard.</li></ul>
<b>Complies With</b>	2004/42/EC (2012) sub-category B(a) - VOC level below 200 g/l.
<b>Product Code</b>	<b>MP0207.</b>
<b>VOC's</b>	80 ± 10 g/l.
<b>Coverage</b>	The rate of consumption will depend on the degree of contamination and the application method. Practical evaluations have shown that T Cleaner 8 can more than equate to similar solvent based cleaners in cleaning effectiveness.
<b>Equipment</b>	Impervious gloves should be worn, to protect the skin from the oils and other residues removed from the surface as well as from the T Cleaner 8. Inhalation protection is not normally required in areas of good factory ventilation.
<b>Application</b>	Normally, effective cleaning is achieved by simple wiping methods as noted below: <ol style="list-style-type: none"><li>1. T Cleaner 8 should be used to dampen the cleaning cloth; it should not be poured onto the surface to be cleaned. It may be sprayed on to the item using a trigger spray bottle.</li><li>2. Cloths that have not become too contaminated can be stored in an air-tight container and used for the initial cleaning of heavily soiled surfaces.</li><li>3. Folding the cloth to form a pad and progressively refolding to use a clean area of the material, using both sides, will ensure maximum economy.</li><li>4. Before painting, remove traces of detergent by wiping with a clean damp cloth.</li><li>5. Eliminate overspray and prevent effluent going down the surface drain.</li></ol>
<b>Drying</b>	Most surfaces will be dry for painting within a few minutes. Should forced drying of the cleaned surface be necessary, temperatures up to 125°C may be used.
<b>Shelf Life</b>	1 year from date of delivery when correctly stored in unopened containers.
<b>Storage</b>	The product should be stored in cool, dry, frost-free conditions, in sealed containers.
<b>Health &amp; Safety</b>	Refer to the product's Safety Data Sheet and safety advice on the product label before use.

## TECHNICAL DATA SHEET

---

### **Trimite T Cleaner 8** **WB Degreaser**

**Technical Support** For technical support in using this product, please contact:  
e: [belfast.sales@trimite.com](mailto:belfast.sales@trimite.com), or  
t: +44 (0)28 9066 3361.

**Date of Issue** Jan 2025.

Information provided in this leaflet is given in good faith but without warranty or assumed liability, as the conditions of application and use are beyond our control. Data are accurate to the best of our knowledge at the time of issue but may be revised in the light of new knowledge and the user should check that data are current before use. The user must satisfy themselves about the product's suitability for their own purpose and refer to the Safety Data Sheet for this product before use. For industrial or professional use only unless specifically stated otherwise.